

ARTICLE	DM153
BASIC INFORMATION	
Width	293 cm
Weight	235 g/m2
Minimum order	0.1 m
Roll length	30 m
ABRASION RESISTANCE	
Standard	EN ISO 12 947
Result	10 000 martindale cycles
COLOUR FASTNESS TO LIGHT	
Standard	ISO 105-B02
Result	4-5
COMPOSITION	
Polyester FR	100%
SHRINKAGE	
Standard	UNI EN ISO 6330:2009
Warp	0,2%
Weft	0,2%
SEAM SLIPPAGE	
Standard	EN ISO 13 936-2
Weft	2,8 mm
Warp	3,2 mm
PILLING	
Standard	EN ISO 12945-2
Result	3

ARTICLE	DM153
FLAME RETARDANT STANDARDS	
Standard	Result
IMO	FTP code 2010 part 7
NF P 92 503	M1
EN 13773	1
UNI 9175	Classe 1
BS 5867 PART 2	B
DIN 4102	B1
ACOUSTIC PARAMETERS	
Standard	Result
EN ISO 354:2004 & 11654:1998	0,50 - CLASS D
MAINTENANCE	
    	
APPLICATION	
Flame Retardant	
Curtains	
Dimout	
Decorative	
IMO	
FLAME RETARDANCY	
Other standard – result	PASSED
PARAMETERS	
Oeko-Tex Standard 100 class I	
Acoustic	