

ARTICLE	DM169
BASIC INFORMATION	
Width	300 cm
Weight	236 g/m ²
Minimum order	0.1 m
Roll length	30 m
Thermal resistance	0.353 m ² K/W
ABRASION RESISTANCE	
Standard	EN ISO 12 947
Result	40 000 martindale cycles
COLOUR FASTNESS TO LIGHT	
Standard	EN ISO 105-B02
Result	3-4
COLOUR FASTNESS TO RUBBING	
Standard	ISO 105 X12
Wet friction	4-5
Dry friction	4-5
COMPOSITION	
Polyester	100%
SHRINKAGE	
Result	1%
SEAM SLIPPAGE	
Standard	EN ISO 13 936-2
Along weft	3 mm
Along warp	4 mm

ARTICLE		DM169
PILLING		
Standard		EN ISO 12 945-2
Result		5
ACOUSTIC PARAMETERS		
Standard		Result
EN ISO 354:2004 & 11654:1998		0.60 KLASA C
ASTM C423-09a		NRC 0.75 SAA 0.74
DB-HR		0.88
MAINTENANCE		
     		

APPLICATION	
Curtains	
Dimout	
PARAMETERS	
Oeko-Tex Standard 100 class II	
Acoustic	
Thermal resistance	